Sigtronics Power Supply Adapter — PG-PSA

Installation Instructions



Power Supply Adapter Features

This genuine Sigtronics engineered and built adapter is used to safely control the power to your Sigtronics systems in vehicles with 24 volt DC or 12 volt positive ground electrical systems.

Sigtronics Equipment that may be used with PG-PSA

- EAI Intercom
- UltraSound Intercom
- S.A.F.E. Communicator
- MRIM-2 Mobile Radio Interface Module

Installation

Attach the Power Supply Adapter in a convenient location using the included hardware. Verify that the adapter unit and cable will not interfere with the normal operation of any vehicle controls or the operation of vehicle compartment doors. Connect the wiring harness color-for-color to the Sigtronics intercom and vehicle power. See table below.

Sigtronics Power Supply Adapter Model: PG-PSA

Input Power: 12 to 28 Volts DC

Warranty: One year parts and labor.

Part Description	Part Number	Quantity		
Interface Cable	N/A	1		
Hex Nut, 6-32, Locking	100067	4		
Phillips Head Screw, 6-32 x 5/8, Black	100105	4		

Standard Equipment Included

Connector Pinout

Pin	Wire Color	Function	Connect To
1	White / Red	Power Input +	Vehicle Power +
2	White / Black	Power Input –	Vehicle Power –
3	Green	Power Output –	Sigtronics Equip- ment Green Wire
4	Red	Power Output +	Sigtronics Equip- ment Red Wire



Specialists in "SOUND" Management 178 East Arrow Highway, San Dimas, CA 91773 (909) 305-9399